



EK AUTOMATIC Take Away

TECHNICAL DATA

Electronic coffee machine with automatic dose setting
 Electronic boiler refill
 Electric heating system
 Double pressure gauge for boiler and pump pressure control
 1 hot water outlet / 2 steam wands
 Electronic boiler temperature regulation
 Boiler temperature indicated by LED display
 Automatic operating temperature boost function
 Control of malfunctions alarms
 Built-in volumetric pump
 Electric cup warmer available on request
 Possibility to deactivate the electric heating system
 Upgraded boiler heating element available on request

Available in the following colours:



Red



Silver




Black



LA SPAZIALE

espresso coffee machines



| | | | |
|----------|-----|------|-----|
| 2 groups | 530 | 770 | 600 |
| 3 groups | 530 | 1000 | 600 |
| 4 groups | 530 | 1235 | 600 |

machine
back

• Dimensions in mm.

Taller cup guard available on request
 Distance of 16 cm between delivery spouts and drip tray for "take away"
 Removable supporting grid for espresso cups

Boiler capacity:
 2 groups 10 litres
 3 groups 15 litres
 4 groups 20 litres

Power supply and power absorption:
 2 groups 400/220/240 V - 50/60 Hz - 3500 W.
 3 groups 400/220/240 V - 50/60 Hz - 4500 W.
 4 groups 400/220/240 V - 50/60 Hz - 6000 W.

OPTIONS:

MATAutomatic system for milk emulsion with adjustable temperature
 ITC Individual temperature control for each delivery group
 AT Preset hot water delivery for infusions
 GA Service scheduled control system and water softener cartridge control
 Chrome body
 Gold body