



EP SEMIAUTOMATIC Take Away

TECHNICAL DATA

Semiautomatic coffee machine with free-flow delivery
 Electronic boiler refill
 Electric heating system
 Double pressure gauge for boiler and pump pressure control
 1 hot water outlet / 2 steam wands
 Electronic boiler temperature regulation
 Boiler temperature indicated by LED display

Automatic operating temperature boost function

Control of malfunctions alarms

Built-in volumetric pump

Electric cup warmer available on request

Possibility to deactivate the electric heating system

Upgraded boiler heating element available on request

Available in the following colours:



Red



Silver



Black

LA PAZIALE

espresso coffee machines



2 groups	530	770	600
3 groups	530	1000	600
4 groups	530	1235	600

 machine
back

• Dimensions in mm.

Taller cup guard available on request
 Distance of 16 cm between delivery spouts and drip tray for "take away"

Removable supporting grid for espresso cups

Boiler capacity:
 2 groups 10 liters
 3 groups 15 liters
 4 groups 20 liters

Power supply and power absorption:
 2 groups 400/220/240 V - 50/60 Hz - 3500 W.
 3 groups 400/220/240 V - 50/60 Hz - 4500 W.
 4 groups 400/220/240 V - 50/60 Hz - 6000 W.

OPTIONS:

MATAutomatic system for milk emulsion with adjustable temperature
 ITC Individual temperature control for each delivery group
 AT Preset hot water delivery for infusions
 GA Service scheduled control system and water softener cartridge control
 Chrome body
 Gold body

